

CONTROL CONCEPTS CONNECT

GATEWAY MODULE

DESCRIPTION

Control Concepts' CONNECT is a fieldbus gateway module that can link up to 10 MicroFUSION units using CCI Link, a dedicated, real-time, deterministic digital bus.

The CONNECT module reduces per-point cost for digital system connectivity and gives full access to monitor parameters that are only available over a dedicated digital bus.

FEATURES

- · Controls up to 10 Zones
- · Protocols:
 - EtherCAT
 - EtherNet/IP
 - Modbus TCP
 - PROFINET (only 6 zones)
 - PROFIBUS (only 6 zones)
- Data Logger
 - · Battery-backed real time clock
 - · Removable SD Card
 - Records data in 100 ms to 1 minute intervals
- Micro USB port for easy setup
- Panel mount or Din-Rail mount





cooled heatsink with 10 node EtherCAT

CONNECT gateway. Maximum power of 480 KW

DIMENSIONS

Dimensions: Inches [mm]





SPECIFICATIONS

ENVIRONMENTAL	
Power Consumption	200 mA Amps at 24 Vdc - Powered from CCI Link
Surrounding Air Operating Temperature	32°F [0°C] - 122°F [50°C]
Humidity	20% to 90% RH Non-Condensing
Rated Operating Altitude	Up to 6000 ft [1750m]
Contaminates	ROHS Compliant, CE Pollution Degree 2
Storage Temperature	- 4 to 176°F [- 20 to 80°C]
Heatsink Options	Panel Mount or Din Rail Mountable

SD Card	
Capacity	16 GB Included. Maximum compatible storage: 64 GB
Logging Channels	Up to 10 devices
Logging Intervals	100 ms to 1 minute

DIGITAL BUS PERFORMANCE		
Command Latency	TBD	
Monitor Latency	TBD	
Update Period	≤ 100 ms	

MODEL NUMBERS

Consult factory for additional fieldbus interfaces

Nodes -

03 - Communicate with up to three nodes06 - Communicate with up to six nodes

10 - Communicate with up to ten nodes

CONTACT/ORDERING INFORMATION

TEL: (952) 474-6200 I (800) 765-2799
FAX: (952) 474-6070 I www.ccipower.com
18760 Lake Drive East, Chanhassen, MN 55317, USA



1-800-765-2799

FG - □ - □[