

ACCESSORIES

AUXILIARY I/O CARD

- Retransmit
 - 2 Analog output channels
 - Scalable 0-10V dc or 0-20mA with up to 15 Vdc compliance voltage
 - Each channel may be assigned either the RMS or AVG value of the load voltage, load current, or true instantaneous load power
- Digital I/O
 - 2 Digital inputs (TTL compatible, pull up to 5V through a 10K Ω resistor)
 - 2 Digital Outputs (Relay driver transistor based, Open collector that sinks up to 48 Vdc at 150 mA)

FIELDBUS INTERFACE

- MODBUS RTU (RS-485), MODBUS TCP (Ethernet), DeviceNet, Profinet, or Ethernet IP
- Simplify your cabling, eliminate A/D conversion error, and gain access to monitor information.
- In the model number, use:
 - S for Modbus RTU
 - D for DeviceNet
 - N for ProfiNet
 - E for Modbus TCP
 - I for Ethernet IP

REMOTE DISPLAY

- Controller display is mountable in a 1/4 DIN cutout
- UL-type 1 & 12 ratings, IP65
- Outside Dimensions: 4.156 [105.6] x 4.156 [105.6]
- Display Mounting Kit includes:
 - Gasket, custom mounting brackets with screws, shielded cable, circuit board retainer
- Sizes: 25 ft [7.62m] (CCI P/N: SMAFUSION-RD25)
5 ft [1.52m] (CCI P/N: SMAFUSION-RD5)

USB CABLE

- 15 ft [4.92m] USB Cable (CCI P/N: 0058004-0000-15)

FUSES AND OTHER ACCESSORIES

- A wide range of fuses and fuse blocks are available.
- Please contact factory for fuse sizing and any other accessory needs and we will be happy to accommodate you.

CONTACT/ORDERING INFORMATION

TEL: (952) 474-6200 | (800) 765-2799 FAX:
(952) 474-6070 | www.ccipower.com 8077
Century Blvd, Chanhassen, MN 55317, USA



**CONTROL
CONCEPTS**